

INT-KLFR-B

INTEGRA ALARM SYSTEM KEYPAD

The **INT-KLFR** keypad has been designed for users who prefer a traditional interface to operate the alarm system, but also expect attractive appearance solutions. Additionally, the built-in proximity card reader allows you to operate the system without the necessity to remember passwords.

- backlit keys and display
- LED indicators of system state
- PANIC, FIRE and MEDICAL (AUX) alarms triggered with keys
- acoustic signaling of selected system events
- 2 programmable zones (with 3EOL configuration support)
- RS-232 connector for interfacing with the **GUARDX** program
- built-in proximity card reader for system operation
- available in white (**INT-KLFR-W**), black (**INT-KLFR-B**), light with silver frame (**INT-KLFR-SSW**), dark with silver frame (**INT-KLFR-BSB**) and white with silver frame (**INT-KLFR-WSW**)



TECHNICAL DATA

Supply voltage	12 V DC
Enclosure dimensions	145 x 143 x 25 mm
Operating temperature range	-10...+55 °C
Standby mode current consumption	60 mA
Max. current consumption	110 mA
Weight	346 g
Maximum humidity	93±3%
Environmental class according to EN50130-5	II



The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.